

MODELS AND CHARACTERISTICS

MODEL	POWER	RANGES	MAXIMUM CURRENT						TIMER	AMMETER	MOTORIZED REGULATION	AUXILIARY DC SUPPLY
			PERMANENT	60m	15m	3m	1m	1s				
LET-400	1 kVA	10 A, 50 A, 200 A, 400 A	400 A	600 A	800 A	1,1 kA	1,4 kA	2,5 kA	-	-	-	-
LET-400-RD	1 kVA	10 A, 50 A, 200 A, 400 A	400 A	600 A	800 A	1,1 kA	1,4 kA	2,5 kA	X	X	-	-
LET-400-RDC	1 kVA	10 A, 50 A, 200 A, 400 A	400 A	600 A	800 A	1,1 kA	1,4 kA	2,5 kA	X	X	-	X
LET-1000-RD	2 kVA	250 A, 500 A, 1000 A	1 kA	1,5 kA	2,25 kA	2,25 kA	2,75 kA	6,25 kA	X	X	-	-
LET-2000-RD	4 kVA	250 A, 500 A, 1000 A, 2000 A	2 kA	2,4 kA	3,6 kA	4,8 kA	6 kA	10,8 kA	X	X	-	-
LET-2000-RDM	4 kVA	250 A, 500 A, 1000 A, 2000 A	2 kA	2,4 kA	3,6 kA	4,8 kA	6 kA	10,8 kA	X	X	X	-
LET-2010-RD	6 kVA	500 A, 1000 A, 2000 A	2 kA	2,5 kA	4 kA	5,5 kA	7 kA	13 kA	X	X	-	-
LET-4000-RD	8 kVA	500 A, 1000 A, 2000 A, 4000 A	4 kA	4,8 kA	7,2 kA	9,6 kA	12 kA	21,6 kA	X	X	-	-
LET-4000-RDM	8 kVA	500 A, 1000 A, 2000 A, 4000 A	4 kA	4,8 kA	7,2 kA	9,6 kA	12 kA	21,6 kA	X	X	X	-
LET-4000-R	8 kW	4000 A	4 kA DC			5 kA DC			X	X	-	-

X Available
- Not available